Product datasheet

Specifications



APC NetShelter Metered Rack PDU, 0U, 1PH, 3.3kW 208V 16A or 3.7kW 230V 16A, 18 C13 and 2 C19 outlets, C20 inlet

AP8858

Overview

Presentation	APC Metered Rack Power Distribution Units (PDUs) provide active metering to enable energy optimization and circuit protection. User-defined alarm thresholds mitigate risk with real-time local and remote alerts to warn of potential circuit overloads. Metered Rack PDUs provide power utilization data to allow Data Center Managers to make informed decisions on load balancing and right sizing IT environments to lower total cost of ownership. Metered Rack PDUs include real power monitoring, a temperature/humidity sensor port, locking IEC receptacles, and ultra low profile circuit breakers. Users can access and configure Metered Rack PDUs through secure Web, SNMP, or Telnet Interfaces which are complimented by APC Centralized Management platforms using InfraStruxure Central, Operations, Capacity, and Energy Efficiency.

Main

Product or component type	PDU
Main Input Voltage	200 V 208 V 230 V
Input current limits	20 A
Network frequency	50/60 Hz
Main Output Voltage	100 V 200 V 208 V 230 V
Input Connection Type	IEC 60320 C20
Number of power socket outlets	18 IEC 60320 C13 2 IEC 60320 C19
Load capacity	3300 VA
[In] rated current	16 A
permissible voltage	100…240 V
Max current draw	16 A
PDU type	Metered
Protection type	Without circuit breaker
Number of rack unit	0U
Provided equipment	Installation guide Rack mounting brackets Serial configuration cable Safety guide

Complementary

Mounting location	Side
Mounting mode	Rack-mounted

Price is “List Price” and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Mounting position	Vertical
Height	902 mm
Width	56 mm
Depth	44 mm
Net weight	2.93 kg

Environmental

Product certifications	METI Denan VDE
Standards	CSA C22.2 No 60950 IEC 60950 UL 60950-1
Relative humidity	5…95 %
Storage Relative Humidity	5…95 %
Ambient air temperature for storage	-25…65 °C
Storage altitude	0…15240 m
Operating altitude	0...10000 ft
Ambient air temperature for operation	-5…60 °C

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	112.4 cm
Package 1 Width	16.2 cm
Package 1 Length	10.7 cm
Package 1 Weight	4.191 kg

Contractual warranty

Warranty (in months)	24

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

Environmental footprint

Total lifecycle Carbon footprint	**843 kg CO2 eq.**
Carbon footprint of the manufacturing phase [A1 to A3]	**48 kg CO2 eq.**
Carbon footprint of the distribution phase [A4]	**0.6 kg CO2 eq.**
Carbon footprint of the installation phase [A5]	**0.1 kg CO2 eq.**
Carbon footprint of the use phase [B2, B3, B4, B6]	**792 kg CO2 eq.**
Carbon footprint of the end-of-life phase [C1 to C4]	**2 kg CO2 eq.**
Environmental Disclosure	**Product Environmental Profile**

Use Better

Materials and Substances

Average percentage of recycled plastic content	**15 %**
Packaging made with recycled cardboard	**Yes**
Packaging without single use plastic	**Yes**
EU RoHS Directive	**Compliant By Exemption**
REACh Regulation	**Free of Substances of Very High Concern above the threshold**
Halogen-free status	**Product contains halogen above thresholds**

Use Again

Repack and remanufacture

Recyclability potential, in %	**53**
Removable battery	**Yes**
Take-back	**No**
WEEE Label	**The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins**

Image of product / Alternate images

Alternative

