Specifications







Eaton PDUMH15HVNET

Eaton Tripp Lite series switched PDU, 1PH, 1U, IEC-340 C14 input, 6.5ft cord, 2.5kW, 12A, 230/208V, 8 outlets (8) C13

General specifications	
PRODUCT NAME	Eaton Tripp Lite series switched PDU
CATALOG NUMBER	PDUMH15HVNET
UPC	037332139276
PRODUCT LENGTH/DEPTH	17.33 in
PRODUCT HEIGHT	1.72 in
PRODUCT WIDTH	14.77 in
PRODUCT WEIGHT	8.9 lb
WARRANTY	2 year limited
COMPLIANCES	CE Marked FCC Class A RoHS TAA Compliant
CERTIFICATIONS	UL 60950-1 NOM CSA Std. C22.2

Product specifications

FORM FACTOR	1U
PACKAGE CONTENTS	• 1U Switched PDU • Mounting brackets • Cord retention plates • C13 to C14 power cable
OPERATING TEMPERATURE	32° to 104°F (0° to 40°C)
MOUNTING DIRECTION	Horizontal
MATERIAL	Metal
INPUT CONNECTION	C14
CORD LENGTH	6.5 ft
AMPERAGE RATING	12A
ELECTRIC CURRENT - MAX	12
PHASE	Single-phase
FREQUENCY RATING	50/60 Hz
NUMBER OF OUTPUTS C13	8
FEATURES	Flex Center
SNMP	Yes
FRONT PANEL LCD DISPLAY	Digital display reports total PDU output current in amps
OUTPUT RECEPTACLES	C13
GROUNDING OPTIONS	Back panel grounding lug
LED INDICATORS	8 LEDs display power on-off status for each output receptacle
MINIMUM REQUIRED RACK DEPTH	17.1 in
NETWORK PORTS	RJ45 Network port, Micro-USB Configuration port, USB A port supports a variety of Envirosense2 environmental and control modules. See Accessories>Management Hardware section for more information about these modules.
RECOMMENDED ELECTRICAL SERVICE	Single-phase 12/10A 208/230V service
OUTPUT RECEPTACLES DETAILS	Compatible with Eaton Tripp Lite Power Cords
RECEPTACLES	• 8 individually switched output receptacles • C13
INPUT CORD LENGTH	6.5 ft
TAA COMPLIANCE	Yes
PRODUCT FEATURES	C14 inlet
COMMUNICATIONS CABLE	Micro-USB- to-USB A configuration/console Access

Resources

	cable
AMPERAGE RATING DETAILS	Agency de-rated to 12A at 200, 208, 220 & 240V; Agency de-rated to 10A at 230V
OPERATING ELEVATION	0-10000 ft. (0-3000 m)
OPERATING TEMPERATURE RANGE	32° to 104°F (0° to 40°C)
OUTPUT NOMINAL VOLTAGE	208/230V
RELATIVE HUMIDITY	5% to 95% non-condensing
FORM FACTORS SUPPORTED	1U rackmount, Includes mounting accessories for 2-4 post racks
OUTPUT CAPACITY DETAILS	2.5kW (208V), 2.3kW (230V) / 12A (10A CE) total capacity
OUTPUT CAPACITY (KW)	2.5
STORAGE TEMPERATURE	-22° to 122°F (-30° to 50°C)
NETWORK SPEED	10 Mbps 100 Mbps (Fast Ethernet)
PRODUCT HIGHLIGHTS	Pre-installed WEBCARDLX with latest version of PADM20 for IP-based Auto Probe feature 2-year limited warranty (Worldwide) Compatible with Eaton Tripp Lite power cords to simplify deployment and enhance reliability Temperature, humidity and contact-closure monitoring options Visual current meter; reversible housing 8 C13 switched outlets with cord retention brackets Switched 10/12A 208/230V PDU; 1U horizontal rackmount TAA Compliant C14 inlet; 6.5ft / 2m C14 power cable included
POWERALERT SOFTWARE	LX Platform Interface: PowerAlert Device Manager
SNMP COMPATIBILITY	Pre-installed LX platform interface provides remote monitoring via Java-free HTML5 web interface, telnet, SSH and SNMP management systems
PDU PLUG TYPE	C14
PDU TYPE	Switched
PDU INPUT VOLTAGE	208
HIGH AVAILABILITY PDU FEATURES	Auto load shedding Auto probe monitoring and reboot (included)
PDU FORM FACTOR	Horizontal (1U)
TOTAL OUTLETS	8

PROJECT NAME:	
PROJECT NUMBER:	
PREPARED BY:	
DATE:	

Eaton Corporation plc Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2026 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.