

## Product Highlights

### Modular

Suitable for both 24-26 AWG stranded and solid cables, the NPG-C61MET502-100 fits a wide range of cables giving you flexibility during installation

### High Conductivity

50 micro-inch thick gold plating for better conductivity and longer lifespan which helps make your network more robust and reliable

### International Standards

Supports IEC60603-7-4 and complies with ANSI/TIA/EIA-568-C.2 standards making deployment into your existing network hassle free



## NPG-C61MET502-100

# CAT6 FTP Modular Plug

## Features

### Modular design

- Fits 24-26 AWG

### Standards

- IEC60603-7-4
- ANSI/TIA/EIA-568-C.2

### Reliable and fast connection

- 50 micro-inch thick gold plating
- Polycarbonate housing
- Nickel plated bronze shield

The NPG-C61MET502-100 CAT6 FTP Modular Plug is a universal network jack with high conductivity, for all your network cabling requirements.

## Modular Plugs

D-Link Category 6 Modular Plugs are suitable for both 24-26 AWG stranded and solid cables. This modular design means they can be used for a wide range of networking needs that span across a whole business system, eliminating the need to constantly switch between plugs when cabling. Compatible with standard RJ45 Wire network crimping tools, D-Link CAT 6 modular plugs fit seamlessly into any well-established standard operating procedure, making cable assembly easy.

## High Conductivity

The RJ45 jack contact terminals are finished with 50 micro-inch thick gold plating, not only increasing conductivity but also the connector's lifespan, this results in more reliable and fast data transfers.

## Universal Standards

Supporting the IEC60603-7-4 and complying with ANSI/TIA/EIA-568-C.2 standards, the D-Link CAT 6 modular plugs easily integrate into any established network cabling system.

## Technical Specifications

### General Specifications

RJ45 Jack Housing & Insert	<ul style="list-style-type: none"><li>• Polycarbonate</li><li>• UL94-2</li></ul>
RJ45 Jack Shield	<ul style="list-style-type: none"><li>• Bronze with Nickel plating</li></ul>
RJ45 Jack Contact Terminal Material	<ul style="list-style-type: none"><li>• Phosphor bronze with 100 micro-inch nickel plating on contact area</li></ul>
RJ45 Jack Contact Terminal Finish	<ul style="list-style-type: none"><li>• 50 micro-inch gold plating</li></ul>
Insertion Cycles	<ul style="list-style-type: none"><li>• 2000 times</li></ul>
Operating Temperature	<ul style="list-style-type: none"><li>• -40 °C to 125°C</li></ul>

### Electrical Specifications

Current Rating (MAX)	<ul style="list-style-type: none"><li>• 2A</li></ul>
AC Input	<ul style="list-style-type: none"><li>• 250V AC</li></ul>
Insulation Resistance	<ul style="list-style-type: none"><li>• &gt; 500 Megaohms,1000V DC/min</li></ul>
Contact Resistance	<ul style="list-style-type: none"><li>• &lt;20 Milliohms</li></ul>

### Order Information

<i>Part Number</i>	<i>Description</i>
NPG-C61MET502-100	CAT6 FTP Modular Plug

Updated 2014/06/16